

Audio - passive

Adapter plates sized			50 x 50 mm	50 x 50 mm	54 x 54 mm	60 x 60 mm
Illustration	Model	Connection	Aluminium	Stainless steel	Aluminium	Aluminium
	Audio L/R (cinch) Required installation depth for cable+plug: 47 mm	Soldering Cable+plug	7444 000 410 7444 000 510	7451 000 410 7451 000 510	7441 000 410 7441 000 510	7442 000 410 7442 000 510
	Audio jack (3.5 mm stereo) Required installation depth for cable+plug: 47 mm	Soldering Cable+plug	7444 000 411 7444 000 511	7451 000 411 7451 000 511	7441 000 411 7441 000 511	7442 000 411 7442 000 511
	Audio jack (6.3 mm stereo)	Soldering	7444 000 417		7441 000 417	
	XLR 3-pin (full size plate) Neutrik® socket (f)	Soldering (XLR socket - f)	7444 000 412	7451 000 412	7441 000 412	7442 000 412
		Soldering (XLR plug - m)	7444 000 416		7441 000 416	7442 000 416
	XLR 3-pin plug (m) - 2-fold (full size plate)	Clamp	7444 000 578		7441 000 578	
	Speakon 4-pin (full size plate) Neutrik® socket (f) Required installation depth: 40 mm (with soldering)	Soldering	7444 000 413	7451 000 413	7441 000 413	7442 000 413
	Loudspeaker Suitable for loudspeaker cables or pin plugs up to 4 mm ²	Screw+clamp	7444 000 414		7441 000 414	7442 000 414
	Volume control (Poti, passive) (cinch L/R) (full size plate) For Line signals, e.g. of notebooks, DVD players Required installation depth: 35 mm	Cable+plug	7444 000 518		7441 000 518	
	Audio 2 x cinch / 1 x jack (3.5 mm stereo) (full size plate) With volume control/Poti, passive Symmetric output for Line signals, e.g. of DVD players	Clamp	7444 000 418		7441 000 418	
	Audio 1 x XLR socket (f) (full size plate) With volume control/Poti, passive Symmetric output	Clamp	7444 000 419		7441 000 419	